



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE  
REQUEST FOR FILING NATIONAL PHASE OF  
PCT APPLICATION UNDER 35 U.S.C. 371 AND 37 CFR 1.494 OR 1.495

Hon. Commissioner of Patents  
Washington, D.C. 20231



00909

JC20 Rec'd PCT/PTO 26 JUL 2001

Atty Dkt: P 282665 /EUR 50725/USw

M# /Client Ref.

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)

From: Pillsbury Winthrop LLP, IP Group:

Date: July 26, 2001

This is a **REQUEST** for **FILING** a PCT/USA National Phase Application based on:

1. International Application	2. International Filing Date	3. Earliest Priority Date Claimed
PCT/EP00/00039	05 January 2000	26 January 1999
<u>country code</u>	Day MONTH Year	Day MONTH Year (use item 2 if no earlier priority)

4. Measured from the earliest priority date in item 3, this PCT/USA National Phase Application Request is being filed within:

(a) ☐ 20 months from above item 3 date (b) ☒ 30 months from above item 3 date,

(c) Therefore, the due date (unextendable) is July 26, 2001

5. Title of Invention FOAMED THERMOPLASTIC POLYURETHANES

6. Inventor(s) Dominicus LIMERKENS  
Johan VAN DIJCK  
Bart VAN EDOM  
Rhona WATSON

Applicant herewith submits the following under 35 U.S.C. 371 to effect filing:

7. ☒ Please immediately start national examination procedures (35 U.S.C. 371 (f)).

8. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2)) is transmitted herewith (file in English but, if in foreign language, file only if not transmitted to PTO by the International Bureau) including:

a. ☐ Request;

b. ☒ Abstract;

c. 19 pgs. Spec. and Claims;

d. \_\_\_ sheet(s) Drawing which are ☐ informal ☐ formal of size ☐ A4 ☐ 11"

9. ☒ A copy of the International Application has been transmitted by the International Bureau.

10. A translation of the International Application into English (35 U.S.C. 371(c)(2))

a. ☐ is transmitted herewith including: (1) ☐ Request; (2) ☐ Abstract;

(3) \_\_\_ pgs. Spec. and Claims;

(4) \_\_\_ sheet(s) Drawing which are:

☐ informal ☐ formal of size ☐ A4 ☐ 11"

b. ☒ is not required, as the application was filed in English.

c. ☐ is not herewith, but will be filed when required by the forthcoming PTO Missing Requirements Notice per Rule 494(c) if box 4(a) is X'd or Rule 495(c) if box 4(b) is X'd.

d. ☐ Translation verification attached (not required now).

09/890067

11. ☒ Please see the attached Preliminary Amendment
12. ☐ Amendments to the claims of the International Application **under PCT Article 19 (35 U.S.C. 371(c)(3)), i.e., before 18th month from first priority date above in item 3, are transmitted herewith (file only if in English) including:**
13. ☒ PCT Article 19 claim amendments (if any) have been transmitted by the International Bureau
14. ☐ Translation of the amendments to the claims **under PCT Article 19 (35 U.S.C. 371(c)(3)), i.e., of claim amendments made before 18th month, is attached (required by 20th month from the date in item 3 if box 4(a) above is X'd, or 30th month if box 4(b) is X'd, or else amendments will be considered canceled).**
15. **A declaration of the inventor (35 U.S.C. 371(c)(4))**  
a. ☐ is submitted herewith ☐ Original ☐ Facsimile/Copy  
b. ☒ is not herewith, but will be filed when required by the forthcoming PTO Missing Requirements Notice per Rule 494(c) if box 4(a) is X'd or Rule 495(c) if box 4(b) is X'd.
16. **An International Search Report (ISR):**  
a. Was prepared by ☒ European Patent Office ☐ Japanese Patent Office ☐ Other  
b. ☒ has been transmitted by the international Bureau to PTO.  
c. ☐ copy herewith (\_\_\_ pg(s).) ☐ plus Annex of family members (\_\_\_ pg(s).).
17. **International Preliminary Examination Report (IPER):**  
a. ☒ has been transmitted (if this letter is filed after 28 months from date in item 3) in English by the International Bureau with Annexes (if any) in original language.  
b. ☐ copy herewith in English.  
c.1 ☐ IPER Annex(es) in original language ("Annexes" are amendments made to claims/spec/drawings during Examination) including attached amended:  
c.2 ☐ Specification/claim pages #\_\_\_ claims #  
Dwg Sheets #  
d. ☐ Translation of Annex(es) to IPER **(required by 30<sup>th</sup> month due date, or else annexed amendments will be considered canceled).**
18. **Information Disclosure Statement** including:  
a. ☐ Attached Form PTO-1449 listing documents  
b. ☐ Attached copies of documents listed on Form PTO-1449  
c. ☐ A concise explanation of relevance of ISR references is given in the ISR.
19. ☐ **Assignment** document and Cover Sheet for recording are attached. Please mail the recorded assignment document back to the person whose signature, name and address appear at the end of this letter.
20. ☐ Copy of Power to IA agent.
21. ☐ **Drawings** (complete only if 8d or 10a(4) not completed): \_\_\_ sheet(s) per set: ☐ 1 set informal; ☐ Formal of size ☐ A4 ☐ 11"
22. Small Entity Status ☒ is **Not** claimed ☐ is claimed (**pre-filing confirmation required**)  
22(a) \_\_\_ (No.) Small Entity Statement(s) enclosed (since 9/8/00 Small Entity Statements(s) not essential to make claim)
23. **Priority** is hereby claimed under 35 U.S.C. 119/365 based on the priority claim and the certified copy, both filed in the International Application during the international stage based on the filing in (country) Europe of:
- |     | Application No. | Filing Date     |     | Application No. | Filing Date |
|-----|-----------------|-----------------|-----|-----------------|-------------|
| (1) | 99101359.0      | 26 January 1999 | (2) |                 |             |
| (3) |                 |                 | (4) |                 |             |
| (5) |                 |                 | (6) |                 |             |
- a. ☒ See Form PCT/IB/304 sent to US/DO with copy of priority documents. If copy has not been received, please proceed promptly to obtain same from the IB.  
b. ☐ Copy of Form PCT/IB/304 attached.

RE: USA National Phase Filing of PCT/EP00/00039

24. Attached: Copy of IPER including set of claims as amended

25 Per Item 17.c2, cancel original pages #\_\_, claims #\_\_, Drawing Sheets #26. **Calculation of the U.S. National Fee (35 U.S.C. 371 (c)(1)) and other fees is as follows:**Based on amended claim(s) per above item(s) ☐ 12, ☐ 14, ☐ 17, ☐ 25 (hilitte)

Total Effective Claims	23	minus 20 =	3	x \$18/\$9	=	\$54	966/967
Independent Claims	3	minus 3 =	0	x \$80/\$40	=	\$0	964/965
If any proper (ignore improper) Multiple Dependent claim is present,				add \$270/\$135	+	0	968/969

BASIC NATIONAL FEE (37 CFR 1.492(a)(1)-(4)): →→ BASIC FEE REQUIRED, NOW →→→→

A. If country code letters in item 1 are not "US", "BR", "BB", "TT", "MX", "IL", "NZ", "IN" or "ZA"

See item 16 re:

1. Search Report was <u>not</u> prepared by EPO or JPO -----	add \$1000/\$500		960/961
2. Search Report was prepared by EPO or JPO -----	add \$860/\$430	+860	970/971

SKIP B, C, D AND E UNLESS country code letters in item 1 are "US", "BR", "BB", "TT", "MX", "IL", "NZ", "IN" or "ZA"

→ <input type="checkbox"/> B. If USPTO did not issue <u>both</u> International Search Report (ISR) <u>and</u> (if box 4(b) above is X'd) the International Examination Report (IPER), -----	add \$1000/\$500	+0	960/961
→ <input type="checkbox"/> C. If USPTO issued ISR but not IPER (or box 4(a) above is X'd), -----	add \$710/\$355	+0	958/959
→ <input type="checkbox"/> D. If USPTO issued IPER but IPER Sec. V boxes <u>not all</u> 3 YES, -----	add \$690/\$345	+0	956/957
→ <input type="checkbox"/> E. If international preliminary examination fee was paid to USPTO and Rules 492(a)(4) and 496(b) <u>satisfied</u> (IPER Sec. V <u>all</u> 3 boxes YES for <u>all</u> claims), -----	add \$100/\$50	+0	962/963

27. SUBTOTAL =	\$914	
28. If Assignment box 19 above is X'd, add Assignment Recording fee of ----\$40	+0	(581)
29. Attached is a check to cover the -----	TOTAL FEES	\$914

Our Deposit Account No. 03-3975

Our Order No. 38266 | 282665

C#

M#



00909

**CHARGE STATEMENT:** The Commissioner is hereby authorized to charge any fee specifically authorized hereafter, or any missing or insufficient fee(s) filed, or asserted to be filed, or which should have been filed herewith or concerning any paper filed hereafter, and which may be required under Rules 16-18 and 492 (missing or insufficient fee only) now or hereafter relative to this application and the resulting Official document under Rule 20, or credit any overpayment, to our Account/Order Nos. shown above for which purpose a duplicate copy of this sheet is attached.

This CHARGE STATEMENT does not authorize charge of the issue fee until/unless an issue fee transmittal form is filed

**Pillsbury Winthrop LLP**  
**Intellectual Property Group**

By Atty: Paul L. SharerReg. No. 36004Sig: *Anna Jewel*
Reg. No.  
43,402

Fax: (703) 905-2500  
 Tel: (703) 905-2180

Atty/Sec: PLS/cdw

NOTE: File in duplicate with 2 postcard receipts (PAT-103) & attachments.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re PATENT APPLICATION of:

LIMERKENS *et al.*

Group Art Unit: TBA

Application No.: TBA

Examiner: TBA

Filed: July 26, 2001

FOR: FOAMED THERMOPLASTIC POLYURETHANES

\* \* \* \* \*

July 26, 2001

**PRELIMINARY AMENDMENT**

Hon. Commissioner of Patents  
Washington, D.C. 20231

Sir:

Prior to examination on the merits, please amend the above-identified patent  
(including the amended claims 1-21 as attached to the IPER) in the manner set forth below.

**IN THE SPECIFICATION:**

At the top of the first page, just under the title, insert

--This application is the National Phase of International Application  
PCT/EP00/00039 filed January 5, 2000 which designated the U.S. and that  
International Application was published under PCT Article 21(2) in English.--

**Page 2, please delete the paragraph starting at line 1, and replace it with the  
following new paragraph:**

--The present invention thus concerns a process for the preparation of foamed thermoplastic  
polyurethanes whereby the foaming of the thermoplastic polyurethane is carried out in the  
presence of thermally expandable microspheres and in the presence of an additional blowing

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re PATENT APPLICATION of:

LIMERKENS *et al.*

Group Art Unit: TBA

Application No.: TBA

Examiner: TBA

Filed: July 26, 2001

FOR: FOAMED THERMOPLASTIC POLYURETHANES

\* \* \* \* \*

July 26, 2001

**PRELIMINARY AMENDMENT**

Hon. Commissioner of Patents  
Washington, D.C. 20231

Sir:

Prior to examination on the merits, please amend the above-identified patent  
(including the amended claims 1-21 as attached to the IPER) in the manner set forth below.

**IN THE SPECIFICATION:**

At the top of the first page, just under the title, insert

--This application is the National Phase of International Application  
PCT/EP00/00039 filed January 5, 2000 which designated the U.S. and that  
International Application was published under PCT Article 21(2) in English.--

**Page 2, please delete the paragraph starting at line 1, and replace it with the  
following new paragraph:**

--The present invention thus concerns a process for the preparation of foamed thermoplastic  
polyurethanes whereby the foaming of the thermoplastic polyurethane is carried out in the

presence of thermally expandable microspheres and in the presence of an additional blowing agent, said microspheres containing a hydrocarbon.--

**Page 8, please delete the paragraph starting at line 14, and replace it with the following new paragraph:**

--A blowing agent is added to the system, which may either be an exothermic or endothermic blowing agent, or a combination of both. Most preferably however, an endothermic blowing agent is added.--

**Page 13, please delete line 21, and replace it with the following new line:**

--Example 4 (comparative)--

**IN THE CLAIMS:**

**Please amend the claims as follows:**

1. (Amended)            Process for the preparation of foamed thermoplastic polyurethanes wherein the foaming of the thermoplastic polyurethane is carried out in the presence of thermally expandable microspheres and in the presence of an additional blowing agent, said microspheres containing a hydrocarbon.
3. (Amended)            Process according to claim 1 wherein an endothermic blowing agent is present.

**LIMERKENS *et al.* – Filed July 26, 2001**

4. (Amended) Process according to claim 1 wherein an exothermic blowing agent is present.
5. (Amended) Process according to claim 3 wherein the endothermic blowing agent comprises bicarbonates or citrates.
6. (Amended) Process according to claim 1 wherein the exothermic blowing agent comprises azodicarbonamide type compounds.
7. (Amended) Process according to claim 1 which is carried out by injection molding.
8. (Amended) Process according to claim 1 which is carried out in a pressurized mold.
9. (Amended) Process according to claim 1 wherein the starting thermoplastic polyurethane is made by using a difunctional isocyanate composition comprising an aromatic difunctional isocyanate.
12. (Amended) Process according to claim 9 wherein the difunctional polyhydroxy compound comprises a polyoxyalkylene diol or polyester diol.
15. (Amended) Process according to claim 1 wherein the amount of microspheres is

between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.

17. (Amended) Process according to claim 1 wherein the amount of blowing agent is between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.

19. (Amended) Foamed thermoplastic polyurethane obtained by reacting a difunctional isocyanate composition with at least one difunctional polyhydroxy compound, in the presence of thermally expandable microspheres containing hydrocarbon, and in the presence of an additional blowing agent, said polyurethane having a density of not more than 700 kg/m<sup>3</sup>.

**Please add the following new claims:**

22. (New) Foamed thermoplastic polyurethane obtained by the process as defined in claim 1 said polyurethane being used in footwear or integral skin applications.

23. (New) Customized foamed thermoplastic polyurethane obtained by the process as defined by claim 1 wherein said polyurethane is formed into any article made with thermoplastic resins including interior and exterior parts of automobiles, housings of electric devices, packaging materials, leisure goods, sporting goods and toys.



REMARKS

After introduction of the amendment set forth above, claims 1-23 will be pending in the application of which claim 1, 19 and 21 are independent. Claims 1, 3-9, 12, 15, 17 and 19 have been amended to eliminate multiple dependency of the claims and to correct grammatical errors. Claims 22-23 have been added as new claims. Support for the above amendments can be found throughout the original application as filed. Applicants submit that no new matter has been introduced by the amendment.

Respectfully submitted,

PILLSBURY WINTHROP, LLP

By: Ana Ferrel, Reg. No. 43,402  
Paul L. Sharer  
Reg. No. 36,004  
Tel. No.: (703) 905-2180  
Fax No.: (703) 905-2500

PLS/JLP  
1600 Tysons Boulevard  
McLean, VA 22102  
(703) 905-2000

Enclosure: Appendix

LIMERKENS *et al.* – Filed July 26, 2001

**APPENDIX**

**VERSION WITH MARKINGS SHOWING CHANGES MADE**

**IN THE SPECIFICATION:**

**The specification is changed as follows:**

Page 2, the paragraph starting at line 1:

The present invention thus concerns a process for the preparation of foamed thermoplastic polyurethanes whereby the foaming of the thermoplastic polyurethane is carried out in the presence of thermally expandable microspheres and in the presence of an additional blowing agent, said microspheres containing a hydrocarbon.

Page 8, the paragraph starting at line 14:

**[In a preferred embodiment, a] A** blowing agent is added to the system, which may either be an exothermic or endothermic blowing agent, or a combination of both. Most preferably however, an endothermic blowing agent is added.

Page 13, line 21:

Example 4 (comparative)

**IN THE CLAIMS:**

**The claims are amended as follows:**

1. (Amended) Process for the preparation of foamed thermoplastic polyurethanes  
**[characterised in that]** wherein the foaming of the thermoplastic polyurethane is carried out in the presence of thermally expandable microspheres and in the presence of an additional blowing agent, said microspheres containing a hydrocarbon.
3. (Amended) Process according to **[any of the preceding claims]** claim 1 wherein an endothermic blowing agent is present.
4. (Amended) Process according to **[any of the preceding claims]** claim 1 wherein an exothermic blowing agent is present.
5. (Amended) Process according to claim 3 **[or 4]** wherein the endothermic blowing agent comprises bicarbonates or citrates.
6. (Amended) Process according to **[any of claims 4-5]** claim 1 wherein the exothermic blowing agent comprises azodicarbonamide type compounds.
7. (Amended) Process according to **[any of the preceding claims]** claim 1 which is carried out by injection **[moulding]** molding.
8. (Amended) Process according to **[any of the preceding claims]** claim 1 which is carried out in a pressurized **[mould]** mold.

9. (Amended) Process according to **[any of the preceding claims]** claim 1 wherein the starting thermoplastic polyurethane is made by using a difunctional isocyanate composition comprising an aromatic difunctional isocyanate.
12. (Amended) Process according to **[claims 9-11]** claim 9 wherein the difunctional polyhydroxy compound comprises a polyoxyalkylene diol or polyester diol.
15. (Amended) Process according to **[any of the preceding claims]** claim 1 wherein the amount of microspheres is between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
17. (Amended) Process according to **[any of the preceding claims]** claim 1 wherein the amount of blowing agent is between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
19. (Amended) Foamed thermoplastic polyurethane **[obtainable]** obtained by reacting a difunctional isocyanate composition with at least one difunctional polyhydroxy compound, in the presence of thermally expandable microspheres containing hydrocarbon, and in the presence of an additional blowing agent, said polyurethane having a density of not more than 700 kg/m<sup>3</sup>.

**Claims 22 and 23 have been added as new claims.**

Foamed thermoplastic polyurethanes*Field of the invention*

The present invention is concerned with a process for the preparation of foamed thermoplastic polyurethanes, novel foamed thermoplastic polyurethanes and reaction systems for preparing  
5 foamed thermoplastic polyurethanes.

*Background of the invention*

Thermoplastic polyurethanes, herein after referred to as TPUs, are well-known thermoplastic  
10 elastomers. In particular, they exhibit very high tensile and tear strength, high flexibility at low temperatures, extremely good abrasion and scratch resistance. They also have a high stability against oil, fats and many solvents, as well as stability against UV radiation and are being employed in a number of end use applications such as the automotive and the footwear industry.

15 As a result of the increased demand for lighter materials, a low density TPU needs to be developed which, in turn, represents a big technical challenge to provide, at minimum, equal physical properties to conventional low density PU.

20 It is already known to produce soles and other parts of polyurethane by a polyaddition reaction of liquid reactants resulting in an elastic solid moulded body. Up till now the reactants used were polyisocyanates and polyesters or polyethers containing OH-groups. Foaming was effected by adding a liquid of low boiling point or by means of CO<sub>2</sub>, thereby obtaining a foam at least partially comprising open cells.

25 Reducing the weight of the materials by foaming the TPU has not given satisfactory results up to now. Attempts to foam TPU using well-known blowing agents as azodicarbonamides (exothermic) or sodiumhydrocarbonate (endothermic) based products were not successful for mouldings with reduced densities below 800 kg/m<sup>3</sup>.

With endothermic blowing agents, a good surface finish can be obtained but the lowest density achievable is about  $800 \text{ kg/m}^3$ . Also, the processing is not very consistent and results in long demoulding times. Very little or no foaming is obtained at the mould surface due to a relatively low mould temperature, resulting in a compact, rather thick skin and a coarse cell core.

5

By using exothermic blowing agents, a lower density foam (down to  $750 \text{ kg/m}^3$ ) with very fine cell structure can be achieved but the surface finish is not acceptable for most applications and demould time is even longer.

10 From the above it is clear that there is a continuous demand for low density TPUs having improved skin quality which can be produced with reduced demould times.

It has now been surprisingly found that foaming TPUs in the presence of thermally expandable microspheres, allows to meet the above objectives. Demould times are significantly reduced  
15 and the process can be carried out at lower temperatures, resulting in a better barrel stability. In addition, the use of microspheres even allows to further reduce the density while maintaining or improving the skin quality and demould time.

The present invention thus concerns a process for the preparation of foamed thermoplastic  
20 polyurethanes whereby the foaming of the thermoplastic polyurethane is carried out in the presence of thermally expandable microspheres.

The low density thermoplastic polyurethanes thus obtained (density not more than  $800 \text{ kg/m}^3$ ) have a fine cell structure, very good surface appearance, a relatively thin skin and show  
25 comparable physical properties to conventional PU which renders them suitable for a wide variety of applications.

The invention provides TPU products having outstanding low temperature dynamic flex properties and green strength at the time of demould, at density  $800 \text{ kg/m}^3$  and below.

The term "green strength", as is known in the art, denotes the basic integrity and strength of the TPU at demould. The polymer skin of a moulded item, for example, a shoe sole and other moulded articles, should possess sufficient tensile strength and elongation and tear strength to survive a 90 to 180 degree bend without exhibiting surface cracks. The prior art processes often require 5 minutes minimum demould time to attain this characteristic.

In addition, the present invention therefore provides a significant improvement in minimum demould time. That is to say, a demould time of 2 to 3 minutes is achievable.

The use of microspheres in a polyurethane foam has been described in EP-A 29021 and US-A 5418257.

Adding blowing agents during the processing of TPUs is widely known, see e.g. WO-A 94/20568, which discloses the production of foamed TPUs, in particular expandable, particulate TPUs, EP-A 516024, which describes the production of foamed sheets from TPU by mixing with a blowing agent and heat-processing in an extruder, and DE-A 4015714, which concerns glass-fibre reinforced TPUs made by injection moulding TPU mixed with a blowing agent.

Nevertheless, none of the prior art documents discloses the use of thermally expandable microspheres to improve the skin quality of foamed low density TPU (density 800 kg/m<sup>3</sup> and even below) nor do these documents suggest the benefits associated with the present invention.

#### *Detailed description*

Thermoplastic polyurethanes are obtainable by reacting a difunctional isocyanate composition with at least one difunctional polyhydroxy compound and optionally a chain extender in such amounts that the isocyanate index is between 90 and 110, preferably between 95 and 105, and most preferably between 98 and 102.

The term 'difunctional' as used herein means that the average functionality of the isocyanate composition and the polyhydroxy compound is about 2.

The term "isocyanate index" as used herein is the ratio of isocyanate-groups over isocyanate-  
5 reactive hydrogen atoms present in a formulation, given as a percentage. In other words, the isocyanate index expresses the percentage of isocyanate actually used in a formulation with respect to the amount of isocyanate theoretically required for reacting with the amount of isocyanate-reactive hydrogen used in a formulation.

10 It should be observed that the isocyanate index as used herein is considered from the point of view of the actual polymer forming process involving the isocyanate ingredient and the isocyanate-reactive ingredients. Any isocyanate groups consumed in a preliminary step to produce modified polyisocyanates (including such isocyanate-derivatives referred to in the art as quasi- or semi-prepolymers) or any active hydrogens reacted with isocyanate to produce  
15 modified polyols or polyamines, are not taken into account in the calculation of the isocyanate index. Only the free isocyanate groups and the free isocyanate-reactive hydrogens present at the actual elastomer forming stage are taken into account.

The difunctional isocyanate composition may comprise any aliphatic, cycloaliphatic or  
20 aromatic isocyanates. Preferred are isocyanate compositions comprising aromatic diisocyanates and more preferably diphenylmethane diisocyanates.

The polyisocyanate composition used in the process of the present invention may consist essentially of pure 4,4'-diphenylmethane diisocyanate or mixtures of that diisocyanate with one  
25 or more other organic polyisocyanates, especially other diphenylmethane diisocyanates, for example the 2,4'-isomer optionally in conjunction with the 2,2'-isomer. The polyisocyanate component may also be an MDI variant derived from a polyisocyanate composition containing at least 95% by weight of 4,4'-diphenylmethane diisocyanate. MDI variants are well known in the art and, for use in accordance with the invention, particularly include liquid products  
30 obtained by introducing carbodiimide groups into said polyisocyanate composition and/or by reacting with one or more polyols.



Preferred polyisocyanate compositions are those containing at least 80% by weight of 4,4'-diphenylmethane diisocyanate. More preferably, the 4,4'-diphenylmethane diisocyanate content is at least 90, and most preferably at least 95% by weight.

- 5 The difunctional polyhydroxy compound used has a molecular weight of between 500 and 20000 and may be selected from polyesteramides, polythioethers, polycarbonates, polyacetals, polyolefins, polysiloxanes, polybutadienes and, especially, polyesters and polyethers, or mixtures thereof. Other dihydroxy compounds such as hydroxyl-ended styrene block copolymers like SBS, SIS, SEBS or SIBS may be used as well.

10

Mixtures of two or more compounds of such or other functionalities and in such ratios that the average functionality of the total composition is about 2 may also be used as the difunctional polyhydroxy compound. For polyhydroxy compounds the actual functionality may e.g. be somewhat less than the average functionality of the initiator due to some terminal unsaturation.

15

Therefore, small amounts of trifunctional polyhydroxy compounds may be present as well in order to achieve the desired average functionality of the composition.

20

Polyether diols which may be used include products obtained by the polymerisation of a cyclic oxide, for example ethylene oxide, propylene oxide, butylene oxide or tetrahydrofuran in the presence, where necessary, of difunctional initiators. Suitable initiator compounds contain 2 active hydrogen atoms and include water, butanediol, ethylene glycol, propylene glycol, diethylene glycol, triethylene glycol, dipropylene glycol, 1,3-propane diol, neopentyl glycol, 1,4-butanediol, 1,5-pentanediol, 1,6-pentanediol and the like. Mixtures of initiators and/or cyclic oxides may be used.

25

30

Especially useful polyether diols include polyoxypropylene diols and poly(oxyethylene-oxypropylene) diols obtained by the simultaneous or sequential addition of ethylene or propylene oxides to difunctional initiators as fully described in the prior art. Random copolymers having oxyethylene contents of 10-80%, block copolymers having oxyethylene contents of up to 25% and random/block copolymers having oxyethylene contents of up to 50%, based on the total weight of oxyalkylene units, may be mentioned, in particular those

having at least part of the oxyethylene groups at the end of the polymer chain. Other useful polyether diols include polytetramethylene diols obtained by the polymerisation of tetrahydrofuran. Also suitable are polyether diols containing low unsaturation levels (i.e. less than 0.1 milliequivalents per gram diol).

5

Other diols which may be used comprise dispersions or solutions of addition or condensation polymers in diols of the types described above. Such modified diols, often referred to as 'polymer' diols have been fully described in the prior art and include products obtained by the in situ polymerisation of one or more vinyl monomers, for example styrene and acrylonitrile, in polymeric diols, for example polyether diols, or by the in situ reaction between a polyisocyanate and an amino- and/or hydroxyfunctional compound, such as triethanolamine, in a polymeric diol.

10

Polyoxyalkylene diols containing from 5 to 50% of dispersed polymer are useful as well.

15 Particle sizes of the dispersed polymer of less than 50 microns are preferred.

Polyester diols which may be used include hydroxyl-terminated reaction products of dihydric alcohols such as ethylene glycol, propylene glycol, diethylene glycol, 1,4-butanediol, neopentyl glycol, 2-methylpropanediol, 3-methylpentane-1,5-diol, 1,6-hexanediol or cyclohexane dimethanol or mixtures of such dihydric alcohols, and dicarboxylic acids or their ester-forming derivatives, for example succinic, glutaric and adipic acids or their dimethyl esters, sebacic acid, phthalic anhydride, tetrachlorophthalic anhydride or dimethyl terephthalate or mixtures thereof.

20

Polyesteramides may be obtained by the inclusion of aminoalcohols such as ethanolamine in polyesterification mixtures.

25

Polythioether diols which may be used include products obtained by condensing thiodiglycol either alone or with other glycols, alkylene oxides, dicarboxylic acids, formaldehyde, aminoalcohols or aminocarboxylic acids.

30

Polycarbonate diols which may be used include those prepared by reacting glycols such as diethylene glycol, triethylene glycol or hexanediol with formaldehyde. Suitable polyacetals may also be prepared by polymerising cyclic acetals.

- 5    Suitable polyolefin diols include hydroxy-terminated butadiene homo- and copolymers and suitable polysiloxane diols include polydimethylsiloxane diols.

10    Suitable difunctional chain extenders include aliphatic diols, such as ethylene glycol, 1,3-propanediol, 1,4-butanediol, 1,5-pentanediol, 1,6-hexanediol, 1,2-propanediol, 2-methylpropanediol, 1,3-butanediol, 2,3-butanediol, 1,3-pentanediol, 1,2-hexanediol, 3-methylpentane-1,5-diol, diethylene glycol, dipropylene glycol and tripropylene glycol, and aminoalcohols such as ethanolamine, N-methyldiethanolamine and the like. 1,4-butanediol is preferred.

- 15    The TPUs suitable for processing according to the invention can be produced in the so-called one-shot, semi-prepolymer or prepolymer method, by casting, extrusion or any other process known to the person skilled in the art and are generally supplied as granules or pellets.

20    Optionally, small amounts, i.e. up to 30, preferably 20 and most preferably 10, wt% based on the total of the blend, of other conventional thermoplastic elastomers such as PVC, EVA or TR may be blended with the TPU.

25    Any thermally expandable microspheres can be used in the present invention. However, microspheres containing hydrocarbons, in particular aliphatic or cycloaliphatic hydrocarbons, are preferred.

The term "hydrocarbon" as used herein is intended to include non-halogenated and partially or fully halogenated hydrocarbons.

- 30    Thermally expandable microspheres containing a (cyclo)aliphatic hydrocarbon, which are particularly preferred in the present invention, are commercially available. Such microspheres

are generally dry, unexpanded or partially unexpanded microspheres consisting of small spherical particles with an average diameter of typically 10 to 15 micron. The sphere is formed of a gas proof polymeric shell (consisting e.g. of acrylonitrile or PVDC), encapsulating a minute drop of a (cyclo)aliphatic hydrocarbon, e.g. liquid isobutane. When these microspheres  
5 are subjected to heat at an elevated temperature level (e.g. 150°C to 200°C) sufficient to soften the thermoplastic shell and to volatilize the (cyclo)aliphatic hydrocarbon encapsulated therein, the resultant gas expands the shell and increases the volume of the microspheres. When expanded, the microspheres have a diameter 3.5 to 4 times their original diameter as a consequence of which their expanded volume is about 50 to 60 times greater than their initial  
10 volume in the unexpanded state. An example of such microspheres are the EXPANCEL-DU microspheres which are marketed by AKZO Nobel Industries of Sweden ('EXPANCEL' is a trademark of AKZO Nobel Industries).

In a preferred embodiment, a blowing agent is added to the system, which may either be an  
15 exothermic or endothermic blowing agent, or a combination of both. Most preferably however, an endothermic blowing agent is added.

Any known blowing agent used in the preparation of foamed thermoplastics may be used in the present invention as blowing agents.

20 Examples of suitable chemical blowing agents include gaseous compounds such as nitrogen or carbon dioxide, gas (e.g. CO<sub>2</sub>) forming compounds such as azodicarbonamides, carbonates, bicarbonates, citrates, nitrates, borohydrides, carbides such as alkaline earth and alkali metal carbonates and bicarbonates e.g. sodium bicarbonate and sodium carbonate, ammonium  
25 carbonate, diaminodiphenylsulphone, hydrazides, malonic acid, citric acid, sodium monocitrate, ureas, azodicarbonic methyl ester, diazabicylooctane and acid/carbonate mixtures. Preferred endothermic blowing agents comprise bicarbonates or citrates.

Examples of suitable physical blowing agents include volatile liquids such as chlorofluorocarbons, partially halogenated hydrocarbons or non-halogenated hydrocarbons like propane, n-butane, isobutane, n-pentane, isopentane and/or neopentane.

- 5 Preferred endothermic blowing agents are the so-called 'HYDROCEROL' blowing agents as disclosed in a.o. EP-A 158212 and EP-A 211250, which are known as such and commercially available ('HYDROCEROL' is a trademark of Clariant).

Azodicarbonamide type blowing agents are preferred as exothermic blowing agents.

10

Microspheres are usually used in amount of from 0.1 to 5.0 parts by weight per 100 parts by weight of thermoplastic polyurethane. From 0.5 to 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane of microspheres are preferred. Most preferably, microspheres are added in amounts from 1.0 to 3.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.

15

The total amount of blowing agent added is usually from 0.1 to 5.0 parts by weight per 100 parts by weight of thermoplastic polyurethane. Preferably, from 0.5 to 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane of blowing agent is added. Most preferably, blowing agent is added in amounts from 1.0 to 3.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.

20

Additives which are conventionally used in thermoplastics processing may also be used in the process of the present invention. Such additives include catalysts, for example tertiary amines and tin compounds, surface-active agents and foam stabilisers, for example siloxane-oxyalkylene copolymers, flame retardants, antistatic agents, plasticizers, organic and inorganic fillers, pigments and internal mould release agents.

25

The foamed thermoplastic polyurethanes of the present invention can be made via a variety of processing techniques, such as extrusion, calendering, thermoforming, flow moulding or injection moulding. Injection moulding is however the preferred production method.

30

The presence of thermally expandable microspheres allows for a reduction in processing temperatures. Typically the process of the present invention is carried out at temperatures between 150 and 175°C.

- 5 Advantageously, the mould is pressurised, preferably with air, and the pressure is released during foaming. Although such process is known and commonly available from several machine producers, it has been surprisingly found that conducting the process of the present invention in a pressurised mould results in TPU articles having an excellent surface finish and physical properties, while having an even further reduced density (down to 350 kg/m<sup>3</sup>).

10 Thermoplastic polyurethanes of any density between about 100 and 1200 kg/m<sup>3</sup> can be prepared by the method of this invention, but it is primarily of use for preparing foamed thermoplastic polyurethanes having densities of less than 800 kg/m<sup>3</sup>, more preferably less than 700 kg/m<sup>3</sup> and most preferably less than 600 kg/m<sup>3</sup>.

15 The thermoplastic polyurethane is customarily manufactured as pellets for later processing into the desired article. The term 'pellets' is understood and used herein to encompass various geometric forms, such as squares, trapezoids, cylinders, lenticular shapes, cylinders with diagonal faces, chunks, and substantially spherical shapes including a particle of powder or a  
20 larger-size sphere. While thermoplastic polyurethanes are often sold as pellets, the polyurethane could be in any shape or size suitable for use in the equipment used to form the final article.

25 According to another embodiment of the present invention, the thermoplastic polyurethane pellet of the present invention comprises a thermoplastic polyurethane body, the thermally expandable microspheres and a binding agent which binds the body and the microspheres. The binding agent comprises a polymeric component that has an onset temperature for its melt processing lower than the onset temperature of the melt processing range of the TPU. The pellets may also include blowing agents and/or additive components such as colorant or  
30 pigments.

The binding agent covers at least part of the thermoplastic polyurethane body. In a preferred embodiment, the thermoplastic polyurethane body and microspheres are substantially encapsulated by the binding agent. By 'substantially encapsulated' we mean that at least three-quarters of the surface of the thermoplastic polyurethane body is coated, and preferably at least about nine-tenths of the resin body is coated. It is particularly preferred for the binding agent to cover substantially all of the polyurethane body and microspheres. The amount of binding agent to the thermoplastic polyurethane may typically range from at least about 0.1% by weight and up to about 10% by weight, based on the weight of the thermoplastic polyurethane pellet. Preferably, the amount of the binding agent is at least about 0.5% by weight and up to 5% by weight, based on the weight of the thermoplastic polyurethane pellet.

Preferably, the binding agent has an onset temperature for its melt processing range that is below the onset temperature of the melt processing range of the thermoplastic polyurethane body. Thus the binding agent may be applied as a melt to the thermoplastic polyurethane body composition while the latter is a solid or substantially a solid. The onset temperature of the melt processing range of the binding agent is preferably above about 20 degree C, and more preferably it is above 60 degree C, and even more preferably it is at least about 80 degree C. The onset temperature of the melt processing range of the polymeric component of the coating preferably has an onset temperature for its melt processing range at least about 20 degree C and even more preferably at least about 40 degree C. below, the onset temperature for the melt processing range of the thermoplastic polyurethane body. If the customized thermoplastic polyurethane pellets are to be dried using a dryer, then the melt processing range of the binding agent is preferably above the temperature of the dryer. In a preferred embodiment, the binding agent is chosen to prevent or slow water absorption so that a drying step before forming the desired article is unnecessary.

The binding agent may then be added to the TPU pellets by several different methods. In one method, the pellets are placed in a container with the coating composition while the pellets are still at a temperature above the onset temperature of the melt processing range of the binding agent. In this case the binding agent may be already melted or may be melted by the heat of the pellets or by heat applied externally to the container. For example, without limitation, the

binding agent may be introduced to the container as a powder when it is to be melted in the container. The binding agent can be any substance capable of binding the thermoplastic polyurethane body and the microspheres. Preferably the binding agent comprises a polymeric component. Examples of suitable polymeric components include polyisocyanates and/or prepolymers thereof.

The foamed thermoplastic polyurethanes obtainable via the process of the present invention are particularly suitable for use in any application of thermoplastic rubbers including, for example, footwear or integral skin applications like steering wheels.

Customized thermoplastic polyurethanes may be produced more efficiently using the process according to the present invention. The customized thermoplastic polyurethanes may be formed into any of the articles generally made with thermoplastic resins. Examples of articles are interior and exterior parts of automobiles, such as inside panels, bumpers, housing of electric devices such as television, personal computers, telephones, video cameras, watches, note-book personal computers; packaging materials; leisure goods; sporting goods and toys

In another embodiment, the present invention concerns a reaction system comprising (a) a TPU and (b) thermally expandable microspheres.

The invention is illustrated, but not limited, by the following examples in which all parts, percentages and ratios are by weight.

## Examples

### Example 1 (comparative)

TPU pellets (Avalon 62AEP; 'Avalon' is a trademark of Imperial Chemical Industries Ltd.) were dry blended with an endothermic blowing agent (1% NC175 powder or 2% INC7175ACR (which is a masterbatch equivalent); both supplied by Tramaco GmbH).



The dry blend was then processed on an injection moulding machine (Desma SPE 231) to form a test moulding of dimensions 19.5 \* 12.0 \* 1 cm.

The processing temperatures for all the examples can be seen on Table 1. The physical properties obtained for all the examples can be seen on Table 2. Abrasion was measured according to DIN53516.

#### Example 2 (comparative)

The TPU of example 1 was dry blended with an exothermic blowing agent (Celogen AZNP130; available from Uniroyal) and was processed in the same way as in Example 1.

The minimum achievable density to avoid severe surface marking is 1000 kg/m<sup>3</sup> with an addition level of 0.3%.

#### Example 3 (comparative)

The TPU of example 1 was dry blended with a mixture of an exothermic and an endothermic blowing agent (0.3% Celogen AZNP130 and 0.7 % NC175) and processed in the same way as Example 1.

#### Example 4

The TPU of example 1 was dry blended with 4% of thermally expandable microspheres (Expancel 092 MB 120; commercially available from Akzo Nobel). This blend was processed in the same way as Example 1.

#### Example 5

The TPU of example 1 was dry blended with 2% of thermally expandable microspheres (Expancel 092 MB120) and an endothermic blowing agent (1% NC175 or 2% INC7175ACR) and processed in the same way as Example 1.

5     Example 6

The TPU of example 1 was dry blended with 2% of thermally expandable microspheres (Expancel 092 MB120) and 1% of an exothermic blowing agent (Celogen AZNP130). Again this was processed in the same way as Example 1.

10

Example 7

The TPU of example 1 was dry blended with 2% of thermally expandable microspheres (Expancel 092 MB120), 0.7 % of an endothermic blowing agent (NC175) and 0.3% of an exothermic blowing agent (Celogen AZNP130). Again this was processed in the same way as Example 1.

15

Example 8

The TPU of example 1 was dry blended with 2% of thermally expandable microspheres (Expancel 092 MB120) and an endothermic blowing agent (1% NC175 or 2% INC7175ACR). This was processed on a Main Group injection moulding machine.

20

Example 9

The TPU of example 1 was dry blended with 2.0% of thermally expandable microspheres (Expancel 092 MB120) and 2% of an exothermic blowing agent (IM7200; commercially available from Tramaco GmbH). This dry blend was processed on a Main Group machine with an air injection system ( Simplex S16).

25

30

Example 10

The TPU of example 1 was dry blended with 2.5% of thermally expandable microspheres (EXP 092 MB120) and 2% of an exothermic blowing agent (IM7200). This dry blend was processed on a Main Group machine with an air injection system ( Simplex S16).

5 Table 1 : Processing Temperatures of Injection Moulding

	Zone 1	Zone 2	Zone 3	Nozzle	Mould Temp.(C)
Ex.1*	180	185	190	185	50
Ex.2*	175	180	185	180	50
Ex.3*	180	185	190	185	50
Ex.4	155	160	165	160	50
Ex.5	160	165	170	165	50
Ex.6	160	165	170	165	50
Ex.7	160	165	170	165	50
Ex.8	155	160	165	160	40
Ex.9	155	160	165	160	25
Ex.10	155	160	165	160	25

\* : comparative example

Table 2 : Properties

	Density (kg/m <sup>3</sup> )	Hardness (Shore A)	Abrasion (mg)	Flex. Resistance (No. of cycles)	Demould time (seconds)	Skin Appearance
Ex.1*	810	61	53	>100.000	180	Excellent
Ex.2*	750	61	70	>100.000	210	Bad
Ex.3*	800	61	60	>100.000	180	Good
Ex.4	800	68	120	>100.000	120	Excellent
Ex.5	700	58	105	>100.000	130	Excellent
Ex.6	670	57	130	>100.000	150	Good
Ex.7	700	58	110	>100.000	130	Excellent
Ex.8	550	51	125	>100.000	180	Excellent
Ex.9	450	46	105	>100.000	180	Excellent
Ex.10	350	40	125	>100.000	180	Excellent

\* : comparative example

### Example 11

5

Example 11 provides for TPU pellets comprising microspheres formulated with binding agent. TPU pellets were pre-heated in a hot air oven at 100°C. Then as a binding agent, an isocyanate prepolymer based on Daltorez® P321 and Suprasec® MPR is prepared at 80°C. The binding agent (1-2% by weight) is then mixed into the TPU pellets to fully wet the surface of the TPU.

10

The additives are then added and mixing continues until a homogeneous distribution of the additives on the surface of the TPU pellets is achieved. This mixture is then discharged into a polythene container and cooled to 10°C to allow the coating to solidify. This 'cake' is then de-agglomerated by hand and is ready for use in the injection molding machine.

15

These coated pellets were processed on the injection molding machine and successfully blown to densities of 0.73 g/cc.

Daltorez ®P321 is a polyester based polyol based on adipic acid and 1,6 hexanediol

Suprasec® MPR is pure MDI

09/890067

531 Rec'd PC

26 JUL 2001

Amended set of claims

1. Process for the preparation of foamed thermoplastic polyurethanes characterised in that the foaming of the thermoplastic polyurethane is carried out in the presence of thermally expandable microspheres and in the presence of an additional blowing agent, said microspheres containing a hydrocarbon.
2. Process according to claim 1 wherein the hydrocarbon is an aliphatic or cycloaliphatic hydrocarbon.
3. Process according to any of the preceding claims wherein an endothermic blowing agent is present.
4. Process according to any of the preceding claims wherein an exothermic blowing agent is present.
5. Process according to claim 3 or 4 wherein the endothermic blowing agent comprises bicarbonates or citrates.
6. Process according to any of claims 4-5 wherein the exothermic blowing agent comprises azodicarbonamide type compounds.
7. Process according to any of the preceding claims which is carried out by injection moulding.
8. Process according to any of the preceding claims which is carried out in a pressurized mould.
9. Process according to any of the preceding claims wherein the starting thermoplastic polyurethane is made by using a difunctional isocyanate composition comprising an aromatic difunctional isocyanate.
10. Process according to claim 9 wherein the aromatic difunctional isocyanate comprises diphenylmethane diisocyanate.

11. Process according to claim 10 wherein the diphenylmethane diisocyanate comprises at least 80% by weight of 4,4'-diphenylmethane diisocyanate.
12. Process according to claims 9-11 wherein the difunctional polyhydroxy compound comprises a polyoxyalkylene diol or polyester diol.
13. Process according to claim 12 wherein the polyoxyalkylene diol comprises oxyethylene groups.
14. Process according to claim 13 wherein the polyoxyalkylene diol is a poly(oxyethylene-oxypropylene) diol.
15. Process according to any of the preceding claims wherein the amount of microspheres is between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
16. Process according to claim 15 wherein the amount of microspheres is between 1.0 and 3.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
17. Process according to any of the preceding claims wherein the amount of blowing agent is between 0.5 and 4.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
18. Process according to claim 17 wherein the amount of blowing agent is between 1.0 and 3.0 parts by weight per 100 parts by weight of thermoplastic polyurethane.
19. Foamed thermoplastic polyurethane obtainable by reacting a difunctional isocyanate composition with at least one difunctional polyhydroxy compound, in the presence of thermally expandable microspheres containing hydrocarbon, and in the presence of an additional blowing agent, said polyurethane having a density of not more than  $700 \text{ kg/m}^3$ .

20. Foamed thermoplastic polyurethane according to claim 19 having a density of not more than  $600 \text{ kg/m}^3$ .
21. Reaction system comprising TPU and thermally expandable microspheres containing a hydrocarbon, said reaction system comprising an additional blowing agent.

FOR UTILITY/DESIGN  
CIP/PCT NATIONAL/PLANT  
ORIGINAL/SUBSTITUTE/SUPPLEMENTAL  
DECLARATIONS

RULE 63 (37 C.F.R. 1.63)  
DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

PW  
FORM

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the INVENTION ENTITLED FOAMED THERMOPLASTIC POLYURETHANES

the specification of which (CHECK applicable BOX(ES))  
X ☐ A. ☐ is attached hereto.  
BOX(ES) → ☐ B. ☐ was filed on \_\_\_\_\_ as U.S. Application No. \_\_\_\_\_ /  
→ ☒ C. ☒ was filed as PCT International Application No. PCT/ EP00/00039 on 05 January 2000  
and (if applicable to U.S. or PCT application) was amended on \_\_\_\_\_

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56. Except as noted below, I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International Application which designated at least one other country than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International Application, filed by me or my assignee disclosing the subject matter claimed in this application and having a filing date (1) before that of the application on which priority is claimed, or (2) if no priority claimed, before the filing date of this application

**PRIOR FOREIGN APPLICATION(S)**

Number	Country	Day/MONTH/Year Filed	Date first Laid-open or Published	Date Patented or Granted	Priority NOT Claimed
99101359.0	EP	26 January 1999			

**If more prior foreign applications, X box at bottom and continue on attached page.**

Except as noted below, I hereby claim domestic priority benefit under 35 U.S.C. 119(e) or 120 and/or 365(c) of the indicated United States applications listed below and PCT international applications listed above or below and, if this is a continuation-in-part (CIP) application, insofar as the subject matter disclosed and claimed in this application is in addition to that disclosed in such prior applications, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in 37 C.F.R. 1.56 which became available between the filing date of each such prior application and the national or PCT international filing date of this application:

**PRIOR U.S. PROVISIONAL, NONPROVISIONAL AND/OR PCT APPLICATION(S)**

Application No. (series code/serial no.)	Day/MONTH/Year Filed	Status	Priority NOT Claimed
		pending, abandoned, patented	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

And I hereby appoint Pillsbury Winthrop LLP, Intellectual Property Group, telephone number (703) 905-2000 (to whom all communications are to be directed), and persons of that firm who are associated with USPTO Customer No. 909 (see below label) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent, and I hereby authorize them to delete from that Customer No. names of persons no longer with their firm, to add new persons of their firm to that Customer No., and to act and rely on instructions from and communicate directly with the person/assignee/attorney/firm/ organization who/which first sends/sent this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instruct the above firm and/or an attorney of that firm in writing to the contrary

USE ONLY FOR  
PILLSBURY WINTHROP

\*00909\*

00909

(1) INVENTOR'S SIGNATURE:

Date:

11.10.01

Name 1 - <u>Dominicus</u>	<u>LIMERKENS</u>	
First	Middle Initial	Family Name
Residence	<u>Meeuwen - Gruitrode</u>	<u>BE</u>
City	State/Foreign Country	Country of Citizenship
Mailing Address	<u>Broekkantstraat 63 - 3680</u>	
(include Zip Code)		

(2) INVENTOR'S SIGNATURE:

Date:

9/10/2001

Name 2 - <u>Johan</u>	<u>VAN DIJCK</u>	
First	Middle Initial	Family Name
Residence	<u>Meeuwen - Gruitrode</u>	<u>BE</u>
City	State/Foreign Country	Country of Citizenship
Mailing Address	<u>Boshovenstraat 23 - 3680</u>	
(include Zip Code)		



**DECLARATION AND POWER OF ATTORNEY**

(Continued)

**ADDITIONAL INVENTORS**

(3) INVENTOR'S SIGNATURE:

Date:

2.10.01

Name <u>3 - 00</u>	<u>Bart</u>		<u>VAN EDOM</u>
	First	Middle Initial	Family Name
Residence	<u>Leuven</u>	<u>BE</u>	<u>BE</u>
	City	State/Foreign Country	Country of Citizenship
Mailing Address	<u>Tiensevest 128/1 - 3000</u>		
(include Zip Code)			

(4) INVENTOR'S SIGNATURE:

Date:

2.10.01

Name <u>4 - 00</u>	<u>Rhona</u>		<u>WATSON</u>
	First	Middle Initial	Family Name
Residence	<u>Huldenberg</u>	<u>BE</u>	<u>GB</u>
	City	State/Foreign Country	Country of Citizenship
Mailing Address	<u>Onze Lieve Vrouwweg 3 - 3040</u>		
(include Zip Code)			

(5) INVENTOR'S SIGNATURE:

Date:

Name			
	First	Middle Initial	Family Name
Residence			
	City	State/Foreign Country	Country of Citizenship
Mailing Address			
(include Zip Code)			

(6) INVENTOR'S SIGNATURE:

Date:

Name			
	First	Middle Initial	Family Name
Residence			
	City	State/Foreign Country	Country of Citizenship
Mailing Address			
(include Zip Code)			

(7) INVENTOR'S SIGNATURE:

Date:

Name			
	First	Middle Initial	Family Name
Residence			
	City	State/Foreign Country	Country of Citizenship
Mailing Address			
(include Zip Code)			